


Proportional Pressure Relief Valve SAE 16-Cartridge - 350 bar


PDB16P-01

Spool Type – Pilot Operated



300 l/min
350 bar

FUNCTION



The PDB16P is a two stage spool type proportional pressure relief valve. If the pressure at port 1 rises above the setting defined by the electrical control signal, the pilot stage opens and allows flow from the back of the main piston to port 2. The resulting pressure imbalance causes the main piston to open against the return spring and allows flow from port 1 to port 2. As a function of the electrical signal the relief pressure at port 1 can be changed steplessly.

FEATURES

- All surfaces zinc-plated and corrosion proof
- All valve parts made of high-strength steel with hardened and ground components to ensure minimal wear and to extend service life
- Rigid design using one-piece body minimizes the effect of eccentricity and maximizes reliability
- Waterproof design standard
- Wide variety of connectors available
- Excellent stability throughout flow range
- Excellent dynamic performance
- Low pressure drop by CFD optimized flow-path
- Screen protected measuring orifice enhances safety

SPECIFICATIONS



Operating pressure:	max. 350 bar
Nominal flow:	max. 300 l/min
Operating pressure ranges:	up to 60 bar, up to 230 bar, up to 350 bar
Control current range:	1050 mA, 8.8 Ω / 2100 mA, 2.2 Ω
Internal leakage:	less than 1 l/min at 350 bar
Media operating temp. range:	-20 °C to +120 °C
Ambient temp. range:	-20 °C to +60 °C
Dither frequency:	160 Hz - 250Hz
Response time:	On: approx. 70 ms, Off: approx. 40 ms
Hysteresis with dither:	2 - 4 % of maximum control current
Repeatability:	1.5 % of maximum pressure range
Reversal error:	≤ 2 % of maximum control current
Response sensitivity:	≤ 1 % of maximum control current
Fluids:	Mineral-based or synthetics with lubricating properties
Viscosity:	7.4 to 420 cSt
Filtration:	Class 18/16/13 up to 19/17/14 according to ISO 4406 or cleaner
Installation:	no orientation restrictions
Material:	Valve body: carbon steel Spool: carbon steel Seals: NBR (standard) FKM (optional) Coil: Steel / Polyamide

Notes:

The PDB16P can also be supplied with an emergency pressure adjustment (version -01M). This allows a mechanical pressure adjustment of the valve if the electrical signal is interrupted. This adjustment should be used only in the case of electrical failure since the manual setting would be additive to the electrical setting and the danger of equipment damage could develop. In order to achieve optimal function, any trapped air should be vented with the bleed screw on the face of the tube (not fitted to version -01M).

Cavity:	FC16-2
Weights:	Valve complete: 790 g Coil only: 230 g


DIMENSIONS



millimeter (inch)
subject to technical modifications

CAVITY

FC16-2



millimeter (inch)
subject to technical modifications

Form tools

Tool	Part No
Rougher FC16-2	176218
Finisher FC16-2	176219

MODEL CODE

PDB16P-01 M - C - N - 330 - 24 PG - 8.8

Basic model

Option

Omission = No option

M = Emergency pressure adjustment

Body and Ports*

C = Cartridge only

SB8 = 1 BSP ports, steel body

SS16 = SAE-16 ports, steel body

AB8 = 1 BSP ports, aluminium body

AS16 = SAE-16 ports, aluminium body

Seals

N = NBR

V = FKM

Pressure range

87 = up to 60 bar

330 = up to 230 bar

500 = up to 350 bar

Coil voltage

12 = 12 V (2.2 Ω)

24 = 24 V (8.8 Ω)

Coil connector

PG = DIN connector (DIN 43650)

PL = Leadwires (2) – 457 mm (18") long

PN = Deutsch Connector DT04-2P-EP04 (axial)

PU = AMP Junior Timer, 2 pole, axial

Coil resistance

2.2 = 2.2 Ω (12 V)

8.8 = 8.8 Ω (24 V)



Standard models

Model code	Material no.
PDB16P-01-C-N-87-12PG-2.2	3144468
PDB16P-01-C-N-330-12PG-2.2	3144469
PDB16P-01-C-N-500-12PG-2.2	3144470
PDB16P-01-C-N-87-24PG-8.8	3144471
PDB16P-01-C-N-330-24PG-8.8	3144472
PDB16P-01-C-N-500-24PG-8.8	3144473

* Standard Line Bodies

Code	Part No	Material	Ports	Pressure
FH162-SB8	3032496	Steel, zinc-plated	1 BSP	420 bar
FH162-SS16	3032655	Steel, zinc-plated	SAE-16	420 bar
FH162-AB8	3037193	Aluminium, clear anodized	1 BSP	245 bar
FH162-AS16	3037195	Aluminium, clear anodized	SAE-16	245 bar

PERFORMANCE



NOTE

The information in this brochure relates to the operating conditions and applications described. For applications or operating conditions not described, please contact the relevant technical department. Subject to technical modifications.

HYDAC Fluidtechnik GmbH
Justus-von-Liebig-Str.
D-66280 Sulzbach/Saar
Tel: 0 68 97 /509-01
Telefax: 0 68 97 /509-598
E-Mail: flutec@hydac.com